Philips
Coaxial cable

1.5 m
F-Type

SWV6300

Enjoy the ultimate viewing experience

with this premium A/V cable

Take your components to optimum performance. This top-of-the-range cable offers the best connection for transferring audio and video signals between components.

Enjoy better picture quality
- 24 carat gold-plated connectors optimise signal
- 99.97% Oxygen-Free Copper (OFC)

Protects against signal loss
- 100% aluminium shielding
- Oxygen-free copper conductor for ideal signal transfer
- Copper-braided shielding
- Foam Polyethylene (FPE) Dielectric

Easy installation
- Non-slip ergonomic grip for easy use
- Plug and play for easy use

Enjoy extended durability
- Heavy-duty brass shell for extended durability
- Super pliable jackets for outstanding flexibility
- Reliable metal strain relief

PHILIPS
sense and simplicity

Coaxial cable
1.5 m F-Type

SWV6300/10

Specifications

Packaging Data
- Quantity: 1
- EAN/UPC/GTIN: 87 10895 93474 9
- Gross weight: 1.06 kg
- Tare weight: 0.21 kg
- Net weight: 0.85 kg
- Length: 330 mm
- Width: 255 mm
- Height: 120 mm

Inner Box
- EAN/UPC/GTIN: 87 10895 97044 0
- Quantity: 2
- Gross weight: 2.92 kg
- Tare weight: 1.22 kg
- Net weight: 1.7 kg
- Length: 345 mm
- Width: 255 mm
- Height: 270 mm

Outer Box
- EAN/UPC/GTIN: 87 10895 97045 7
- Quantity: 4
- Gross weight: 7.3 kg
- Tare weight: 3.9 kg
- Net weight: 3.4 kg
- Length: 530 mm
- Width: 365 mm
- Height: 290 mm

Product highlights

100% aluminium shielding
This protective layer of aluminium guards against electromagnetic interference for improved signal quality.

Twisted high-purity OFC
This oxygen-free copper conductor provides the highest accuracy in signal transfer with minimal resistance.

Copper-braided shielding
This protective layer of copper blocks radio frequency interference for improved signal quality.

FPE Dielectric
Foam Polyethylene (FPE) dielectric is a superior insulation material that protects against signal loss.

Easy grip
This non-slip grip makes connecting your components easy and ergonomically comfortable.

Plug and play
Plug and play offers easy installation of components without time-consuming installations.

Heavy-duty brass shell
The heavy-duty brass shell protects the internal connection of the cable. It ensures durability and the reliability of your connection.

Super pliable jackets
Super pliable PVC jackets are abrasion-resistant for outstanding flexibility and protection against everyday wear and tear.

Metal strain relief
Full metal connector ensures extended durability by preventing damage during use and installation.

24 carat gold-plated connector
24 carat gold-plated connectors ensure the best signal quality for your components.

99.97% OFC solid conductor
99.97% Oxygen-free copper (OFC) cable core provides optimum signal quality.

Issue date 2008-10-11
Version: 1.0.4
12 NC: 9082 100 06386
EAN: 87 10895 93470 1

© 2008 Koninklijke Philips Electronics N.V.
All Rights reserved.
Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips Electronics N.V. or their respective owners.

www.philips.com